

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genetron® 134a

MSDS Number : 000000009876

Product Use Description : Refrigerant, Propellant

Manufacturer or supplier's details : Honeywell International Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
+1-973-455-6300
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : weak

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

Symbol(s) :



Signal word : Warning

Hazard statements : Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.Precautionary statements : **Storage:**
Protect from sunlight. Store in a well-ventilated place.Hazards not otherwise classified : May cause cardiac arrhythmia.
May cause frostbite.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTSFormula : CF₃CH₂F

Chemical nature : Substance

Chemical Name	CAS-No.	Concentration
1,1,1,2-Tetrafluoroethane	811-97-2	99.80 %

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

- | | |
|--------------|--|
| Skin contact | : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician. |
| Eye contact | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician. |
| Ingestion | : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately. |

Notes to physician

- | | |
|-----------|--|
| Treatment | : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed. |
|-----------|--|

SECTION 5. FIREFIGHTING MEASURES

- | | |
|--------------------------------------|--|
| Suitable extinguishing media | : The product is not flammable.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Specific hazards during firefighting | : Contents under pressure.
This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
In case of fire hazardous decomposition products may be |

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

produced such as:
Hydrogen halides
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides

Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is >= 19.5%.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.
- Methods for cleaning up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

- Handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get in eyes, on skin, or on clothing.

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

Wear personal protective equipment.
Use only in well-ventilated areas.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, expose them to open flame or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against fire and explosion

- : The product is not flammable.
Can form a combustible mixture with air at pressures above atmospheric pressure.

Storage**Requirements for storage areas and containers**

- : Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Protective measures**

- : Do not breathe vapour.
Avoid contact with skin, eyes and clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.

Engineering measures

- : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.

Eye protection

- : Wear as appropriate:

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

Safety glasses with side-shields
 If splashes are likely to occur, wear:
 Goggles or face shield, giving complete protection to eyes

- | | |
|--------------------------|--|
| Hand protection | : <ul style="list-style-type: none"> Leather gloves In case of contact through splashing: Protective gloves Neoprene gloves Polyvinyl alcohol or nitrile- butyl-rubber gloves |
| Skin and body protection | : <ul style="list-style-type: none"> Avoid skin contact with leaking liquid (danger of frostbite). Wear cold insulating gloves/ face shield/ eye protection. |
| Respiratory protection | : <ul style="list-style-type: none"> In case of insufficient ventilation, wear suitable respiratory equipment. Wear a positive-pressure supplied-air respirator. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. For rescue and maintenance work in storage tanks use self-contained breathing apparatus. |
| Hygiene measures | : <ul style="list-style-type: none"> Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Keep working clothes separately. |

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : time weighted average	4,240 mg/m ³ (1,000 ppm)	2007	WEEL:US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquefied gas
Color	: colourless
Odor	: weak
pH	: Note: neutral
Melting point/freezing point	: -101 °C
Boiling point/boiling range	: -26.2 °C
Flash point	: Note: not applicable
Evaporation rate	: > 1 Method: Compared to CCl4.
Lower explosion limit	: Note: None
Upper explosion limit	: Note: None
Vapor pressure	: 5,915 hPa at 21.1 °C(70.0 °F) 14,713 hPa at 54.4 °C(129.9 °F)
Vapor density	: 3.5
Density	: 1.2 g/cm3
Water solubility	: 1.5 g/l

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

Partition coefficient: n-octanol/water	:	log Pow: 1.06 Note: The product is more soluble in octanol.
Ignition temperature	:	> 750 °C
Auto-ignition temperature	:	> 750 °C
Decomposition temperature	:	> 250 °C Note: To avoid thermal decomposition, do not overheat.
Molecular weight	:	102.02 g/mol
Global warming potential (GWP)	:	1,300
Ozone depletion potential (ODP)	:	0

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials to avoid	:	Potassium Calcium Powdered metals Finely divided aluminium Magnesium Zinc
Hazardous decomposition	:	Halogenated compounds

Genetron® 134a

00000009876

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

products Hydrogen fluoride
 Carbonyl halides
 Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity : LC50: > 500000 ppm
Exposure time: 4 h
Species: rat

Sensitisation : Cardiac sensitization
Species: dogs
Note: No-observed-effect level 50 000 ppm Lowest observable effect level 75 000 ppm

Repeated dose toxicity : Species: rat
NOEL: 40000 ppm

Genotoxicity in vitro : Note: In vitro tests did not show mutagenic effects

Further information : Note: Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. Avoid skin contact with leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Further information on ecology

Additional ecological information : Accumulation in aquatic organisms is unlikely. This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

SECTION 13. DISPOSAL CONSIDERATIONS

- Disposal methods : Observe all Federal, State, and Local Environmental regulations.
- Note : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

DOT	UN/ID No.	: UN 3159
	Proper shipping name	: 1,1,1,2-Tetrafluoroethane
	Class	: 2.2
	Packing group	
	Hazard Labels	: 2.2
 IATA	UN/ID No.	: UN 3159
	Description of the goods	: 1,1,1,2-Tetrafluoroethane
	Class	: 2.2
	Hazard Labels	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
 IMDG	UN/ID No.	: UN 3159
	Description of the goods	: 1,1,1,2-Tetrafluoroethane
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C, S-V
	Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION**Inventories**

- US. Toxic Substances : On TSCA Inventory

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

Control Act

- Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory
- Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.
- Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory
- Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory
- Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act : On the inventory, or in compliance with the inventory
- China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory
- NZIOC - New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

- SARA 302 Components** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
- SARA 313 Components** : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
- SARA 311/312 Hazards** : Acute Health Hazard
Sudden Release of Pressure Hazard

Genetron® 134a**000000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

California Prop. 65

: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

New Jersey RTK

: 1,1,1,2-Tetrafluoroethane 811-97-2

Pennsylvania RTK

: 1,1,1,2-Tetrafluoroethane 811-97-2

WHMIS Classification

: A: Compressed Gas
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Global warming potential : 1,300**Ozone depletion potential (ODP)** : 0**SECTION 16. OTHER INFORMATION**

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Genetron® 134a**00000009876**

Version 2.6

Revision Date 06/06/2014

Print Date 05/28/2015

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 12/06/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group