

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 1                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : Pyroil™  
STARTING FLUID

### Recommended use of the chemical and restrictions on use

|  |   |
|--|---|
| <b>Details of the supplier of the safety data sheet</b><br>Niteo Products, LLC<br>P.O. Box 191629<br>Dallas TX 75219<br>United States of America | <b>Emergency telephone number</b><br>CHEMTREC DIRECT 1-800-424-9300<br><br><b>Product Information</b><br>1-844-696-4836 |
|--|---|

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Flammable aerosols : Category 1  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 2  
Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1

### GHS Label element

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : Extremely flammable aerosol.  
May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 2                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.

**Precautionary Statements**

**Prevention:**  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
 IF exposed or concerned: Get medical advice/ attention.  
 Do NOT induce vomiting.

**Storage:**  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**  
 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

| Chemical Name                                | CAS-No.    | Classification   | Concentration (%) |
|--|------------|--|-------------------|
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8 | Flam. Liq. 2; H225<br>STOT SE 3; H336<br>Asp. Tox. 1; H304 | 77.53             |

**SAFETY DATA SHEET**

Revision Date: 08/01/2015

Print Date: 1/12/2016

SDS Number: R0340954

Pyroil™ STARTING FLUID

Version: 1.1

PYSFR11

|                |          |   |       |
|----------------|----------|---|-------|
|                |          | Aquatic Acute 2; H401<br><br>Aquatic Chronic 2;<br>H411                                       |       |
| ETHYL ETHER    | 60-29-7  | Flam. Liq. 1; H224<br><br>Acute Tox. 4; H302<br><br>STOT SE 3; H336                           | 19.55 |
| n-HEPTANE      | 142-82-5 | Flam. Liq. 2; H225<br><br>Skin Irrit. 2; H315<br><br>STOT SE 3; H336<br><br>Asp. Tox. 1; H304 | 3.10  |
| CARBON DIOXIDE | 124-38-9 | Press. Gas Liquefied<br>gas; H280   | 2.01  |
| ETHANOL        | 64-17-5  | Flam. Liq. 2; H225<br><br>Eye Irrit. 2A; H319<br><br>STOT SE 3; H336                          | 1.17  |
| ETHYL CHLORIDE | 75-00-3  | Flam. Gas 1; H220<br><br>Carc. 2; H351  | 0.29  |
| TOLUENE        | 108-88-3 | Flam. Liq. 2; H225<br><br>Skin Irrit. 2; H315<br><br>Eye Irrit. 2A; H319<br><br>Repr. 2; H361 | 0.13  |

|  |                           |
|--|---------------------------|
|  | Page: 4                   |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

|  |  |                   |  |
|--|--|-------------------|--|
|  |  | STOT SE 3; H336   |  |
|  |  | STOT RE 2; H373   |  |
|  |  | Asp. Tox. 1; H304 |  |

---

#### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
If unconscious place in recovery position and seek medical advice.  
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 5                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

Cough  
 loss of appetite  
 confusion  
 irregular heartbeat  
 respiratory failure  
 May be fatal if swallowed and enters airways.  
 May cause drowsiness or dizziness.  
 Suspected of causing cancer.  
 Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Aldehydes  
 carbon dioxide and carbon monoxide  
 organic compounds  
 Hydrocarbons  
 formaldehyde-like
- Specific extinguishing methods :  
  
 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
 Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 6                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Remove all sources of ignition.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Suppress (knock down) gases/vapours/mists with a water spray jet.  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
- Other information : Comply with all applicable federal, state, and local regulations.  
Suppress (knock down) gases/vapours/mists with a water spray jet.

---

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Take precautionary measures against static discharges.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.  
Container may be opened only under exhaust ventilation hood.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Keep container tightly closed in a dry and well-ventilated

|  |                           |
|--|---------------------------|
|  | Page: 7                   |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.  
Electrical installations / working materials must comply with the technological safety standards.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

| Components                                   | CAS-No.                | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis        |         |       |
|--|------------------------|----------------------------------|--|--------------|---------|-------|
| TOLUENE                                      | 108-88-3               | TWA                              | 20 ppm   | ACGIH        |         |       |
|  |                        | REL                              | 100 ppm<br>375 mg/m3                           | NIOSH/GUID E |         |       |
|  |                        | STEL                             | 150 ppm<br>560 mg/m3                           | NIOSH/GUID E |         |       |
|  |                        | TWA                              | 200 ppm  | OSHA/Z2      |         |       |
|  |                        | Ceiling                          | 300 ppm  | OSHA/Z2      |         |       |
|  |                        | MAX. CONC                        | 500 ppm  | OSHA/Z2      |         |       |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8             | TWA                              | 500 ppm  | OSHA_TRANS   |         |       |
|  |                        | TWA                              | 300 ppm  | ACGIH        |         |       |
|  |                        | TWA                              | 2,000 mg/m3                                    | OSHA_TRANS   |         |       |
|  |                        | TWA                              | 1,370 mg/m3                                    | ACGIH        |         |       |
|  |                        | ETHYL ETHER                      | 60-29-7  | TWA          | 400 ppm | ACGIH |
|  |                        | STEL                             |  | 500 ppm      | ACGIH   |       |
| PEL  | 400 ppm<br>1,200 mg/m3 | OSHA_TRANS                       |  |              |         |       |
| TWA  | 400 ppm<br>1,200 mg/m3 | TN OEL                           |  |              |         |       |
|  |                        | STEL                             | 500 ppm<br>1,500 mg/m3                         | TN OEL       |         |       |
| n-HEPTANE                                    | 142-82-5               | REL                              | 85 ppm<br>350 mg/m3                            | NIOSH/GUID E |         |       |
|  |                        | Ceil_Time                        | 440 ppm<br>1,800 mg/m3                         | NIOSH/GUID E |         |       |
|  |                        | PEL                              | 500 ppm<br>2,000 mg/m3                         | OSHA_TRANS   |         |       |
|  |                        | TWA                              | 400 ppm  | ACGIH        |         |       |
|  |                        | STEL                             | 500 ppm  | ACGIH        |         |       |
| CARBON DIOXIDE                               | 124-38-9               | TWA                              | 5,000 ppm                                      | ACGIH        |         |       |
|  |                        | STEL                             | 30,000 ppm                                     | ACGIH        |         |       |
|  |                        | REL                              | 5,000 ppm                                      | NIOSH/GUID   |         |       |

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 8                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

|                |         |      |                            |                 |
|----------------|---------|------|----------------------------|-----------------|
|                |         |      | 9,000 mg/m3                | E               |
|                |         | STEL | 30,000 ppm<br>54,000 mg/m3 | NIOSH/GUID<br>E |
|                |         | PEL  | 5,000 ppm<br>9,000 mg/m3   | OSHA_TRANS      |
| ETHANOL        | 64-17-5 | REL  | 1,000 ppm<br>1,900 mg/m3   | NIOSH/GUID<br>E |
|                |         | PEL  | 1,000 ppm<br>1,900 mg/m3   | OSHA_TRANS      |
|                |         | STEL | 1,000 ppm                  | ACGIH           |
|                |         | TWA  | 1,000 ppm<br>1,900 mg/m3   | Z1A             |
| ETHYL CHLORIDE | 75-00-3 | TWA  | 100 ppm                    | ACGIH           |
|                |         | PEL  | 1,000 ppm<br>2,600 mg/m3   | OSHA_TRANS      |
|                |         | TWA  | 1,000 ppm<br>2,600 mg/m3   | Z1A             |

#### Biological occupational exposure limits

| Components | CAS-No.    | Control parameters        | Biological specimen | Sampling time                                    | Permissible concentration | Basis |
|------------|------------|---------------------------|---------------------|--|---------------------------|-------|
| TOLUENE    | 108-88-3   | o-Cresol, with hydrolysis | Creatinine in urine | Sampling time: End of shift.                     | 0.3 mg/g                  |       |
| Remarks:   | Background |                           |                     |  |                           |       |
|            |            | toluene                   | Urine               | Sampling time: End of shift.                     | 0.03 mg/l                 |       |
|            |            | toluene                   | Blood               | Sampling time: Prior to last shift of work week. | 0.02 mg/l                 |       |

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.  
In the case of dust or aerosol formation use respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 9                   |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:  
impervious clothing  
Safety shoes  
Flame-resistant clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : aerosol
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- : No data available
- Boiling point/boiling range : 94.3 °F / 34.6 °C  
(1,013.232 hPa)  
Calculated Phase Transition Liquid/Gas
- Flash point : -49 °F / -45 °C  
Calculated Flash Point
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 36.5 %(V)  
Calculated Explosive Limit
- Lower explosion limit : 1.05 %(V)  
Calculated Explosive Limit
- Vapour pressure : 717.2616 hPa (25 °C)  
Calculated Vapor Pressure

|  |                           |
|--|---------------------------|
|  | Page: 10                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

Relative vapour density : No data available

Relative density : No data available

Density : 0.7114 g/cm<sup>3</sup> (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.  
excessive heat

Incompatible materials : Acids  
Alkali metals  
Ammonia  
Bases  
halogens  
inorganic materials  
Oxidizing agents  
sodium  
Sulphur compounds

Hazardous decomposition products : Aldehydes  
carbon dioxide and carbon monoxide

|  |                           |
|--|---------------------------|
|  | Page: 11                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

formaldehyde-like  
Hydrocarbons  
organic compounds

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

### Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Acute oral toxicity : LD 50 (Rat): > 8,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 3400 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rat): > 4,000 mg/kg

### ETHYL ETHER:

Acute oral toxicity : LD50 (Rat): 1,200 - 1,700 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 32,000 mg/l  
Exposure time: 4 h

### n-HEPTANE:

Acute oral toxicity : LD 50 (Rat): Expected > 5,000 mg/kg  
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 29.29 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): Expected > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: Information given is based on data obtained from similar substances.

### ETHANOL:

Acute oral toxicity : LD 50 (Rat): 7,060 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 117 - 125 mg/l

|  |                           |
|--|---------------------------|
|  | Page: 12                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

Exposure time: 4 h

LC 50 (Mouse): 39 mg/l

Exposure time: 4 h

Acute dermal toxicity : LD Lo (Rabbit): 20 g/kg

**ETHYL CHLORIDE:**

Acute inhalation toxicity : LC 50 (Rat): > 19000 ppm  
 Exposure time: 4 h  
 Test atmosphere: vapour  
 Method: OECD Test Guideline 403

**TOLUENE:**

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 8000 ppm  
 Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): 12,124 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Result: Repeated exposure may cause skin dryness or cracking.

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Mildly irritating to skin

**ETHYL ETHER:**

Result: Irritating to skin

**n-HEPTANE:**

Result: Irritating to skin

**CARBON DIOXIDE:**

Result: Not irritating to skin

**ETHANOL:**

Result: Slightly irritating to skin

**ETHYL CHLORIDE:**

Result: Mildly irritating to skin

**TOLUENE:**

Result: Irritating to skin

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

|  |                           |
|--|---------------------------|
|  | Page: 13                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

Result: Mildly irritating to eyes

ETHYL ETHER:

Result: Severely irritating to eyes

n-HEPTANE:

Result: Mildly irritating to eyes

CARBON DIOXIDE:

Result: Not irritating to eyes

ETHANOL:

Result: Irritating to eyes

ETHYL CHLORIDE:

Result: Mildly irritating to eyes

TOLUENE:

Result: Irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:**

n-HEPTANE:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**

n-HEPTANE:

Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro  
 Test species: rat hepatocytes  
 Method: OECD Test Guideline 473  
 Result: negative

: Test Type: Ames test  
 Method: OECD Test Guideline 471  
 Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Components:**

ETHYL CHLORIDE:

Carcinogenicity -  
 Assessment

: Limited evidence of carcinogenicity in animal studies

|  |                           |
|--|---------------------------|
|  | Page: 14                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**Components:**

TOLUENE:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:**

ETHYL ETHER:

Assessment: May cause drowsiness or dizziness.

n-HEPTANE:

Assessment: May cause drowsiness or dizziness.

ETHANOL:

Assessment: May cause drowsiness or dizziness.

TOLUENE:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Components:**

TOLUENE:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**Product:**

May be fatal if swallowed and enters airways.

**Components:**

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

May be fatal if swallowed and enters airways.

n-HEPTANE:

May be fatal if swallowed and enters airways.

TOLUENE:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

|  |                           |
|--|---------------------------|
|  | Page: 15                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

**Components:**

ETHYL CHLORIDE:

Remarks: Liver

Remarks: Central nervous system

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

n-HEPTANE:

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 1.5 mg/l  
Exposure time: 48 h  
Test Type: static test

LC 50 (Mysidopsis bahia (opossum shrimp)): 0.1 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Water flea (Daphnia magna)): 1 mg/l  
Exposure time: 21 d  
Test Type: static test  
Test substance: WAF  
Method: OECD Test Guideline 211  
Remarks: Information given is based on data obtained from similar substances.

Ecotoxicology Assessment  
Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

ETHANOL:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 12,000 - 16,000 mg/l  
Exposure time: 96 h

|  |                           |
|--|---------------------------|
|  | Page: 16                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l  
Exposure time: 48 h  
Test Type: static test

**ETHYL CHLORIDE:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Daphnia magna)): 58 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 118 mg/l  
End point: Growth inhibition  
Exposure time: 72 h  
Test Type: static test  
Method: Directive 67/548/EEC, Annex V, C.3.

**TOLUENE:**

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l  
Exposure time: 96 h  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Ceriodaphnia dubia)): 3.78 mg/l  
Exposure time: 48 h  
Remarks: Mortality

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): > 433 mg/l  
End point: Growth inhibition  
Exposure time: 96 h

NOEC (Scenedesmus quadricauda (Green algae)): > 400 mg/l  
End point: Growth inhibition  
Exposure time: 7 d

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1.39 mg/l  
Exposure time: 40 d  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Water flea (Ceriodaphnia dubia)): 0.74 mg/l  
Exposure time: 7 d

**Persistence and degradability**

**n-HEPTANE:**

Biodegradability : Result: Readily biodegradable

**ETHYL CHLORIDE:**

Biodegradability : Inoculum: activated sludge  
Result: Not readily biodegradable.

|  |                           |
|--|---------------------------|
|  | Page: 17                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

Biodegradation: 0 %  
Exposure time: 28 d  
Method: Directive 67/548/EEC Annex V, C.4.E.

**TOLUENE:**

Biodegradability : Result: Readily biodegradable

**Bioaccumulative potential**

**ETHYL ETHER:**

Partition coefficient: n-octanol/water : log Pow: 0.89

**n-HEPTANE:**

Partition coefficient: n-octanol/water : log Pow: 4.66

**ETHANOL:**

Partition coefficient: n-octanol/water : log Pow: -0.31

**ETHYL CHLORIDE:**

Partition coefficient: n-octanol/water : log Pow: 1.43

**TOLUENE:**

Bioaccumulation : Species: Ide, silver or golden orfe (Leuciscus idus)  
Bioconcentration factor (BCF): 94  
Exposure time: 3 d  
Concentration: 0.05 mg/l  
Method: Not reported

Partition coefficient: n-octanol/water : log Pow: 2.73

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : The product should not be allowed to enter drains, water courses or the soil.

|  |                           |
|--|---------------------------|
|  | Page: 18                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

## SECTION 14. TRANSPORT INFORMATION

### International transport regulations

#### REGULATION

| ID NUMBER | PROPER SHIPPING NAME | *HAZARD CLASS | SUBSIDIARY HAZARDS | PACKING GROUP | MARINE POLLUTANT / LTD. QTY. |
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|
|-----------|----------------------|---------------|--------------------|---------------|------------------------------|

#### MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

|    |      |          |   |  |                  |
|----|------|----------|---|--|------------------|
| UN | 1950 | Aerosols | 2 |  | LIMITED QUANTITY |
|----|------|----------|---|--|------------------|

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

|    |      |          |     |  |                  |
|----|------|----------|-----|--|------------------|
| UN | 1950 | Aerosols | 2.1 |  | LIMITED QUANTITY |
|----|------|----------|-----|--|------------------|

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

|    |      |          |     |  |                  |
|----|------|----------|-----|--|------------------|
| UN | 1950 | Aerosols | 2.1 |  | LIMITED QUANTITY |
|----|------|----------|-----|--|------------------|

#### INTERNATIONAL MARITIME DANGEROUS GOODS

|    |      |          |     |  |                  |
|----|------|----------|-----|--|------------------|
| UN | 1950 | AEROSOLS | 2.1 |  | LIMITED QUANTITY |
|----|------|----------|-----|--|------------------|

#### TRANSPORT CANADA - INLAND WATERWAYS

|    |      |          |     |  |                  |
|----|------|----------|-----|--|------------------|
| UN | 1950 | AEROSOLS | 2.1 |  | LIMITED QUANTITY |
|----|------|----------|-----|--|------------------|

#### TRANSPORT CANADA - RAIL

|    |      |          |     |  |                  |
|----|------|----------|-----|--|------------------|
| UN | 1950 | AEROSOLS | 2.1 |  | LIMITED QUANTITY |
|----|------|----------|-----|--|------------------|

|  |                           |
|--|---------------------------|
|  | Page: 19                  |
|  | Revision Date: 08/01/2015 |
| <b>SAFETY DATA SHEET</b>   | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

**TRANSPORT CANADA - ROAD**

|    |      |          |     |  |
|----|------|----------|-----|--|
| UN | 1950 | AEROSOLS | 2.1 | MARINE POLLUTANT:(ALIPHATIC PETROLEUM NAPHTHA)LIMITED QUANTITY |
|----|------|----------|-----|--|

**U.S. DOT - INLAND WATERWAYS**

|    |      |   |     |  |
|----|------|---|-----|--|
| UN | 1950 | Aerosols, flammable (engine starting fluid) | 2.1 |  |
|----|------|---|-----|--|

**U.S. DOT - RAIL**

|    |      |   |     |  |
|----|------|---|-----|--|
| UN | 1950 | Aerosols, flammable (engine starting fluid) | 2.1 |  |
|----|------|---|-----|--|

**U.S. DOT - ROAD**

|    |      |          |     |  |
|----|------|----------|-----|--|
| UN | 1950 | AEROSOLS | 2.1 |  |
|----|------|----------|-----|--|

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

|                  |     |
|------------------|-----|
| Marine pollutant | yes |
|------------------|-----|

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

| Components  | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-------------|---------|--------------------|-----------------------------|
| ETHYL ETHER | 60-29-7 | 100                | 511.380779                  |

**SARA 311/312 Hazards** : Chronic Health Hazard  
 Fire Hazard  
 Acute Health Hazard

|  |  |                           |
|--|--|---------------------------|
|  |  | Page: 20                  |
| <b>SAFETY DATA SHEET</b>   |  | Revision Date: 08/01/2015 |
|  |  | Print Date: 1/12/2016     |
|  |  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   |  | Version: 1.1              |
| PYSFR11  |  |                           |

**SARA 313** : This material does not contain any chemical components with  
**Component(s)SARA 313** known CAS numbers that exceed the threshold (De Minimis)  
reporting levels established by SARA Title III, Section 313.

**Pennsylvania Right To Know**

|   |            |                 |
|---|------------|-----------------|
| SOLVENT NAPHTHA (PETROLEUM),<br>LIGHT ALIPHATIC | 64742-89-8 | 70.00 - 90.00 % |
| ETHYL ETHER                                     | 60-29-7    | 10.00 - 20.00 % |
| n-HEPTANE                                       | 142-82-5   | 1.00 - 5.00 %   |
| CARBON DIOXIDE                                  | 124-38-9   | 1.00 - 5.00 %   |
| ETHANOL   | 64-17-5    | 1.00 - 5.00 %   |

**New Jersey Right To Know**

|   |            |                 |
|---|------------|-----------------|
| SOLVENT NAPHTHA (PETROLEUM),<br>LIGHT ALIPHATIC           | 64742-89-8 | 70.00 - 90.00 % |
| ETHYL ETHER   | 60-29-7    | 10.00 - 20.00 % |
| n-HEPTANE   | 142-82-5   | 1.00 - 5.00 %   |
| CARBON DIOXIDE  | 124-38-9   | 1.00 - 5.00 %   |
| ETHANOL   | 64-17-5    | 1.00 - 5.00 %   |
| DISTILLATES (PETROLEUM),<br>HYDROTREATED LIGHT NAPHTHENIC | 64742-53-6 | 0.10 - 1.00 %   |
| TOLUENE   | 108-88-3   | 0.10 - 1.00 %   |

**California Prop 65**

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

**Inventories**


|  |                           |
|--|---------------------------|
|  | Page: 21                  |
| <b>SAFETY DATA SHEET</b>   | Revision Date: 08/01/2015 |
|  | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

## SECTION 16. OTHER INFORMATION

### Further information

Revision Date: 08/01/2015

|  |  |               |          |                     |          |                        |          |
|--|--|---------------|----------|---------------------|----------|------------------------|----------|
| <b>NFPA:</b>   | <b>HMIS III:</b>   |               |          |                     |          |                        |          |
| <p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p> | <table border="1"> <tr> <td><b>HEALTH</b></td> <td><b>2</b></td> </tr> <tr> <td><b>FLAMMABILITY</b></td> <td><b>4</b></td> </tr> <tr> <td><b>PHYSICAL HAZARD</b></td> <td><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight,<br/>2 = Moderate, 3 = High<br/>4 = Extreme, * = Chronic</p> | <b>HEALTH</b> | <b>2</b> | <b>FLAMMABILITY</b> | <b>4</b> | <b>PHYSICAL HAZARD</b> | <b>0</b> |
| <b>HEALTH</b>  | <b>2</b>   |               |          |                     |          |                        |          |
| <b>FLAMMABILITY</b>  | <b>4</b>   |               |          |                     |          |                        |          |
| <b>PHYSICAL HAZARD</b>   | <b>0</b>   |               |          |                     |          |                        |          |

### NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements referred to under sections 2 and 3.

|  |                           |
|--|---------------------------|
|  | Page: 22                  |
| <b>SAFETY DATA SHEET</b>   | Revision Date: 08/01/2015 |
|  | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID   | Version: 1.1              |
| PYSFR11  |                           |

|       |   |
|-------|---|
| H220  | Extremely flammable gas.  |
| H224  | Extremely flammable liquid and vapor.   |
| H225  | Highly flammable liquid and vapor.  |
| H280  | Contains gas under pressure; may explode if heated.                           |
| H302  | Harmful if swallowed.   |
| H304  | May be fatal if swallowed and enters airways.                                 |
| H315  | Causes skin irritation.   |
| H319  | Causes serious eye irritation.  |
| H333  | May be harmful if inhaled.  |
| H336  | May cause drowsiness or dizziness.  |
| H351  | Suspected of causing cancer.  |
| H361  | Suspected of damaging fertility or the unborn child.                          |
| H361d | Suspected of damaging the unborn child.                                       |
| H373  | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H400  | Very toxic to aquatic life.   |
| H401  | Toxic to aquatic life.  |
| H402  | Harmful to aquatic life.  |
| H410  | Very toxic to aquatic life with long lasting effects.                         |
| H411  | Toxic to aquatic life with long lasting effects.                              |
| H412  | Harmful to aquatic life with long lasting effects.                            |

#### Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

|  |                           |
|--|---------------------------|
|  | Page: 23                  |
| <b>SAFETY DATA SHEET</b>   | Revision Date: 08/01/2015 |
|  | Print Date: 1/12/2016     |
|  | SDS Number: R0340954      |
| Pyroil™ STARTING FLUID<br><br>PYSFR11  | Version: 1.1              |

LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
**WHMIS : Workplace Hazardous Materials Information System**